according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 1/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

Article No.:

025-06-002 / 025-06-006 / 025-06-007

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Hydraulic (functional) fluids

Relevant identified uses:

Life cycle stage [LCS]

PW: Widespread use by professional workers

Product Categories [PC]

PC 17: Hydraulic fluids

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

FOX Factory GmbH

Eckstrasse 18 66976 Rodalben

Germany

Telephone: +49(0) 6331 14983-0
Telefax: +49(0) 6331 14983-10
E-mail: info@foxracingshox.de
Website: www.ridefox.de

E-mail (competent person): info@foxracingshox.de

1.4. Emergency telephone number

24h: Antipoison Center Munich +49 89 19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]-:

Hazard classes and hazard categories		Classification pro- cedure
Aspiration hazard (Asp. Tox. 1)		On basis of test data.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS08 Health hazard

Signal word: Danger

Hazard components for labelling:

Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light

paraffinic

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 2/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

hazard statements for health hazards	
H304	May be fatal if swallowed and enters airways.

Supplemental Hazard information (EU): -

Precautionary stat	ements
P102	Keep out of reach of children.

Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER.	
P331	Do NOT induce vomiting.	

Precautionary statements Disposal	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008- [CLP]	Concen- tration
CAS No.: 64742-54-7 EC No.: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1 Danger EUH066	40 - < 50 Wt %
CAS No.: 64742-55-8 EC No.: 265-158-7	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1 Danger H304	40 - < 50 Wt %
CAS No.: 128-39-2 EC No.: 204-884-0	2,6-di-tert-butylphenol Aquatic Acute 1, Aquatic Chronic 1, Skin Irrit. 2 (!) Warning H315-H410 M-factor (acute): 1 M-factor (chronic): 1	0.1 - < 1 Wt %
CAS No.: 255881-94-8 EC No.: 401-850-9	S-(tricyclo[5.2.1.0 2,6]deca-3-en-8(or 9)-yl) O-(isopropyl or isobutyl or 2-ethylhexyl) O-(isopropyl or isobutyl or 2-ethylhexyl)phosphorodithioate Aquatic Acute 1, Aquatic Chronic 1 Warning H410	0.1 - < 1 Wt %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing.

After eye contact:

In case of contact with eyes, rinse immediately thoroughly with plenty of edible oil and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 3/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

After ingestion:

Rinse mouth.

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Get immediate medical advice/ attention.

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Pneumonia Pulmonary oedema

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media:

Water spray jet

5.2. Special hazards arising from the substance or mixture

Combustible

Hazardous combustion products:

In case of fire: Gases/vapours, harmful

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Solvents/Thinner

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 4/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Packaging materials:

Keep/Store only in original container.

Storage class: 10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection DIN EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374

Suitable material: NBR (Nitrile rubber)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Usually no personal respirative protection necessary.

In case of inadequate ventilation wear respiratory protection.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: amber

Odour: Petroleum Odour threshold: not determined

Safety relevant basis data

parameter		at °C	Method	Remark
рН	not applicable			
Melting point	not applicable			
Freezing point	not determined			
Initial boiling point and boiling	> 232 °C			estimated
range				

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 5/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

parameter		at °C	Method	Remark
Decomposition temperature	not determined			
Flash point	125 °C			
Evaporation rate	not determined			
Auto-ignition temperature	not determined			
Upper/lower flammability or explosive limits	not determined			
Vapour pressure	not determined			
Vapour density	not determined			
Density	0.837 kg/l			
Bulk density	not determined			
Water solubility	The study does not need to be conducted because the substance is known to be insoluble in water.			
Partition coefficient: n-octanol/ water	not determined			
Dynamic viscosity	not determined			
Kinematic viscosity	14 mm²/s	40 °C		

9.2. Other information

DMSO extract by IP346: <3%

SECTION 10: Stability and reactivity

10.1. Reactivity

Combustible

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidising agent, strong Reducing agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 6/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
128-39-2	2,6-di-tert-butylphenol	EC₅₀: 0.45 mg/l 2 d
		NOEC: 0.035 mg/l 21 d
255881-94-8	S-(tricyclo[5.2.1.0 2,6]deca-3-en-8(or 9)-yl) O-(isopropyl or isobutyl or 2-ethylhexyl) O-(isopropyl or isobutyl or 2-ethylhexyl)phosphorodithioate	NOEC: 0.002 mg/l 21 d

Assessment/classification:

There are no data available on the mixture itself.

12.2. Persistence and degradability

	3		
CAS No.	Substance name	Biodegradation	Remark
64742-54-7	Distillates (petroleum), hydrotreated heavy paraff inic	No	
64742-55-8	Distillates (petroleum), hydrotreated light paraffin ic	No	
128-39-2	2,6-di-tert-butylphenol	No	
255881-94-8	S-(tricyclo[5.2.1.0 2,6]deca-3-en-8(or 9)-yl) O-(isop ropyl or isobutyl or 2-ethylhexyl) O-(isopropyl or is obutyl or 2-ethylhexyl)phosphorodithioate	No	

Biodegradation:

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

CAS	No.	Substance name	Log K _{OW}	Bioconcentration factor (BCF)
128-3	39-2	2,6-di-tert-butylphenol	4.5	660

Bioconcentration factor (BCF):

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 7/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.
128-39-2	2,6-di-tert-butylphenol	The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.
255881-94-8	S-(tricyclo[5.2.1.0 2,6]deca-3-en-8(or 9)-yl) O- (isopropyl or isobutyl or 2-ethylhexyl) O-(isopropyl or isobutyl or 2-ethylhexyl)phosphorodithioate	The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Recommended list for waste code/waste designation according to AVV:

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

15 02 02 *	absorbents, filter materials (including oil filters not otherwise specified), wiping cloths, protective clothing contaminated by dangerous substances
13 02 05 *	mineral-based non-chlorinated engine, gear and lubricating oils
16 03 05 *	organic wastes containing hazardous substances

^{*:} Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

No dangerous good in sense of these transport regulations.

Land transport (ADR/ RID)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)	
14.1. UN-No.			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	
14.2. UN proper ship	pping name		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	
14.3. Transport haza	ard class(es)		
not relevant			
14.4. Packing group			
not relevant			
14.5. Environmental	hazards		
not relevant			
14.6. Special precau	itions for user		
not relevant			_

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 8/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.

15.1.2. National regulations

[DE] National regulations

Störfallverordnung

for substances contained in the product:

This product is not assigned to a hazard category.

Water hazard class (WGK)

WGK:

3 - stark wassergefährdend

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

- -ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route)
- -CAS: Chemical Abstract Service
- -CLP: Classification, labelling and Packaging
- -DNEL: Derived No Effect Level
- -EC50: Effective Concentration 50%
- -ECHA: European Chemical Agency
- -LC50: Lethal Concentration 50%
- -LD50: Lethal Dose 50%
- -PBT: persistent, bioaccumulative, toxic
- -PNEC: Predicted No Effect Concentration
- -REACH: Registration, Evaluation and Authorization of Chemicals
- -SVHC: Substance of Very High Concern
- -VOC: Volatile organic compounds
- -vPvB: very persistent, very bioaccumulative

16.3. Key literature references and sources for data

HAZARD ASSESSMENT OUTCOME DOCUMENT for 2,6-di-tert-butylphenol

REACH Dissemination Portal

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 24-May-2019 Print date: 24-May-2019

Version: 1 Page 9/9



Fox R3 High Performance Suspension Fluid 5WT ISO 15 Formula

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]-:

Hazard classes and hazard categories	Hazard statements	Classification pro- cedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	On basis of test data.

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H410	Very toxic to aquatic life with long lasting effects.	

Supplemental Hazard information (EU)		
EUH066	Repeated exposure may cause skin dryness or cracking.	

16.6. Training advice

No data available

16.7. Additional information

This Safety Data Sheet was drawn up by TÜV SÜD Industrie Service GmbH (see below), based on data from the supplier, who is named in section 1 and who is responsible for this document.

TÜV SÜD Industrie Service GmbH

Department Environmental Service

Westendstraße 199

80686 Munich - Germany